


























Brache in poliester

	WLL (t) singola braca						WLL (t) coppia di brache				WLL (t) 3- 4- tratti		
	TIRO DIRITTO	CAPPIO	CANESTRO			TIRO DIRITTO		TIRO DIRITTO		CAPPIO		TIRO DIRITTO	
			< 7°	7° ÷ 45°	45° ÷ 60°	7° ÷ 45°	45° ÷ 60°	7° ÷ 45°	45° ÷ 60°	7° ÷ 45°	45° ÷ 60°	7° ÷ 45°	45° ÷ 60°
BRACHE TONDE AD ANELLO													
BRACHE PIATTE CON ASOLE													
BRACHE A PIU' TRATTI													
	M=1	M=0,8	M=2	M=1,4	M=1	M=0,7	M=0,5	M=1,4	M=1	M=1,12	M=0,8	M=2,1	M=1,5
1.000 kg / 1 t	1	0,8	2	1,4	1	0,7	0,5	1,4	1	1,12	0,8	2,1	1,5
2.000 kg / 2 t	2	1,6	4	2,8	2	1,4	1	2,8	2	2,24	1,6	4,2	3
3.000 kg / 3 t	3	2,4	6	4,2	3	2,1	1,5	4,2	3	3,36	2,4	6,3	4,5
4.000 kg / 4 t	4	3,2	8	5,6	4	2,8	2	5,6	4	4,48	3,2	8,4	6
5.000 kg / 5 t	5	4	10	7	5	3,5	2,5	7	5	5,6	4	10,5	7,5
6.000 kg / 6 t	6	4,8	12	8,4	6	4,2	3	8,4	6	6,72	4,8	12,6	9
8.000 kg / 8 t	8	6,4	16	11,2	8	5,6	4	11,2	8	8,96	6,4	16,8	12
10.000 kg / 10 t	10	8	20	14	10	7	5	14	10	11,2	8	21	15
15.000 kg / 15 t	15	12	30	21	15	10,5	7,5	21	15	16,8	12	31,5	22,5
20.000 kg / 20 t	20	16	40	28	20	14	10	28	20	22,4	16	42	30
25.000 kg / 25 t	25	20	50	35	25	17,5	12,5	35	25	28	20	52,5	37,5
30.000 kg / 30 t	30	24	60	42	30	21	15	42	30	33,6	24	63	45
40.000 kg / 40 t	40	32	80	56	40	28	20	56	40	44,8	32	84	60
50.000 kg / 50 t	50	40	100	70	50	35	25	70	50	56	40	105	75
60.000 kg / 60 t	60	48	120	84	60	42	30	84	60	67,2	48	126	90
80.000 kg / 80 t	80	64	160	112	80	56	40	112	80	89,6	64	168	120
100.000 kg / 100 t	100	80	200	140	100	70	50	140	100	112	80	210	150

Coefficiente di sicurezza 7:1

www.tessiturabegni.it

SOLLEVAMENTO, ANCORAGGIO, FISSAGGIO DEI CARICHI